Winchester Trellis

Model# **11174/11174M**

DuraTrel™

1 PERSON

POWER TOOLS REQUIRED

1 HOUR

1 BOX

Assembly Instruction Manual

Please read instructions thoroughly before beginning assembly.

Check boxes carefully for contents listed. Some parts are packaged inside of others.

Assemble on a clean, flat, non-abrasive surface to prevent scratching.

Tighten each screw until snug and the part is firmly secured. Do not apply excessive force. Overtightening may cause deformation or damage to the component.

In the event of missing or damaged parts please call or email our customer service department at the contact info below.

Tools Required

-Battery or Electric Drill (#2 phillips bit)
-Tape Measure
-Hammer or Rubber Mallet (Recommended for cross rails)
-Shovel or Post Hole Digger (Recommended)
-PVC, Super or Crazy Glue

QUESTIONS? COMMENTS? CONTACT US!

115 Vision Parkway
P.O. Box 300
Sheboygan Falls, WI 53085

1-877-258-6020
www.dura-trel.com
sales@dura-trel.com

Part #	Description	Dimension	Box #	Qty
1	Left Post	2" sq. x 84"	1	1
2	Right Post	2" sq. x 84"	1	1
3	Center Cross Rail	⅞" x 1 ½" x 56 ¾"	1	10
4	Bottom Cross Rail	⅞" x 1 ½" x 56 ¾"	1	1
5	Bottom Support Rail	⅞" x 3" x 56 ¾"	1	1
6	Vertical Rail	1" x 1" x 84"	1	1
7	Vertical Rail	1" x 1" x 82"	1	2
8	Vertical Rail	1" x 1" x 80"	1	2
9	Vertical Rail	1" x 1" x 78"	1	2
10	Hardware Bag (Includes):		1	1
	▪ Post Cap	2" square		2
	▪ Arrowhead Cap	1" x 1"		7
	▪ Painted Screw	#8 - ¾"		17
11	Wall Mount Bag (Includes):		1	1
	▪ Spacer Tube	¾" x 2 ½"		4
	▪ Screw	#10 – 6"		4
	▪ Screw Cap	#10		4
	▪ Screw Backer	#10		4





1 Lay out one right post (part 2). Starting at bottom, insert bottom support rail (part 5), bottom cross rail (part 4) and center cross rails (part 3).

NOTE: Make sure all pilot holes are towards the back of the trellis.



2 Slide left post (part 1) over corresponding support and cross rails.



3 Starting with center hole, insert 84” vertical rail (part 6) through cross rails.



4 Working outward away from center, insert 82” vertical rails (part 7) through cross rails.



5 Insert 80” vertical rails (part 8) through cross rails.



6 Insert 78” vertical rails (part 9) through cross rails.



7 Using ¾" painted screws, screw together trellis. Be sure that all parts are fully inserted into posts before securing.



8 Using PVC, super or crazy glue, glue post caps onto posts and arrowhead caps onto vertical rails.



9 To secure to wall, slide 6” screw through clear screw backer. Insert screw through pre-drilled hole in post. To set trellis away from wall, slide screw through spacer tube. After securing, snap screw cap over the screw backer.
NOTE: The wall mounting screws included will not fasten to stone, brick or concrete walls.

Warranty Statement

20 Year Guarantee

Please call manufacturer direct with questions concerning missing or defective parts at Toll Free: 877-258-6020.

Dura-trel, Inc. products are warranted to be free from manufacturing defects resulting in delaminating, peeling, flaking, corroding, cracking, crazing, or extreme amounts of fading or bleaching causing the PVC to change to its natural color for a period of 20 years from the date of purchase.

Normal weathering is defined as exposure to sunlight and extremes of weather and atmosphere which will cause any colored surface to gradually fade.

CONDITIONS NOT COVERED BY THIS WARRANTY:

A. Physical abuse, misuse, neglect, or improper storage.
B. Improper installation or installation not in strict adherence to the instructions written by Dura-Trel, Inc.
C. This warranty does not apply if materials are painted, varnished, or coated with any substance.
D. Dura-Trel, Inc. is not responsible for damages to product during shipping.
E. Damage attributable to atmospheric pollutants, hail, lightning, hurricane, tornado, wind borne objects, earthquake, fire, mildew, casualty, act of God, building or ground settlement, or subjection to stress or weight.

CLAIMS AND REMEDIES:

If a Dura-Trel, Inc. product is determined to have a manufacturing defect which is covered by this warranty, Dura-Trel, Inc. will replace the material containing the defect (labor not included) F.O.B from the point of manufacture. Dura-trel, Inc. will not be responsible for any cost incurred in the removal or reinstallation of the product.

Important: All claims must be sent to the following address and should describe the defect claim.

Dura-Trel, Inc., P.O. Box 122, Sheboygan Falls, WI 53085

Dura-Trel, Inc. reserves the right to discontinue or change its design and/or color. If the original color or style is not available, Dura-Trel, Inc. shall have the right to substitute a product designated by Dura-Trel, Inc.

Dura-Trel, Inc. shall not be liable for any incidental, special, or consequential damages arising out of the use of these products.